

Footnotes

- All shroud panels included.
- Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tire condition. This specification can be subject to a variance of (+ or -) 10%.
- Battery weight not included.
- Due to manufacturing tolerances and continual product improvement, this specification can be subject to variance of + or - 3%.
- Battery pack is 18 lbs. with 12AH batteries.
- Deep cycle (AGM or gel cell type recommended).
- 18 AH battery pack weighs 28 lbs.
- Tested in accordance with ANSI/RESNA, WC Vol 2, Section 4 and ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.
- Up to 14 miles per charge on 18 AH batteries.
- Battery weight may vary based on manufacturer.
- Width of base (not including seat).
- Does not account for anti-tip clearance.
- Includes standard seat weight.
- Must be billed to Medicare as either a beneficiary requested upgrade with a properly executed ABN, or as an upgrade at no additional charge to the beneficiary.
- At midframe.
- Light package.

PRIDE® MOBILITY SCOOTERS

LIVE YOUR BEST®

END-TO-END



	Go Chair®	Go-Go® ES 2	Go-Go® Ultra X	Go-Go Elite Traveller®	Go-Go® Sport	Go-Go® LX with CTS Suspension	Victory® 10	Victory® Sport ¹⁶	Maxima	Pursuit® ¹⁶	Pursuit® XL ¹⁶	Pursuit® Sport 36 Volt ¹⁶	Sport Rider ³	Sport Rider Dual Seat ³
FRONT TIRES	3" x 5" SOLID	2" x 7.5" SOLID	2" x 8" SOLID (3W) 2" x 7" SOLID (4W)	2" x 8" SOLID (3W) 2" x 7" SOLID (4W)	3" x 8" SOLID (3W) 3" x 9" SOLID (4W)	2" x 8" SOLID (3W) 2" x 7" SOLID (4W)	3.5" x 10" SOLID	3.5" x 10" SOLID	3" x 10" SOLID	3" x 13" SOLID	13" PNEUMATIC	13" PNEUMATIC	2.75" x 14" PNEUMATIC	2.75" x 14" PNEUMATIC
REAR TIRES	3" x 8" SOLID	3" x 7.5" SOLID	2.5" x 8" SOLID	2.5" x 8" SOLID	3" x 9" SOLID	2.5" x 8" SOLID	3.5" x 10" SOLID	4" x 10" SOLID	4" x 10" SOLID	13" SOLID	13" PNEUMATIC	13" PNEUMATIC	2.75" x 14" PNEUMATIC	2.75" x 14" PNEUMATIC
MAXIMUM SPEED²	UP TO 3.5 MPH	UP TO 4 MPH	UP TO 4 MPH	UP TO 4 MPH	UP TO 4 MPH	UP TO 4.4 MPH	UP TO 5.25 MPH	UP TO 8 MPH	UP TO 5.25 MPH	UP TO 7.25 MPH	UP TO 8.5 MPH	UP TO 9 MPH	UP TO 9.4 MPH	UP TO 7.45 MPH
GROUND CLEARANCE^{4,12,15}	1.75"	1.5" at mid-frame	2"	2"	3"	1.5" at motor	3" at mid-frame	2.25"	3.25"	3.56"	5.25"	5.25" at mid frame 2.5" at rear frame	5"	5"
3-W TURNING RADIUS⁴	N/A	31"	33"	33"	36"	33"	42"	N/A	49.25"	N/A	N/A	N/A	62.2"	62.2"
4-W TURNING RADIUS⁴	26.75" WITH FOOT PLATFORM	N/A	44"	44"	52"	44.75"	54"	51.75"	54"	67.25"	82.5"	83"	N/A	N/A
3-W LENGTH/WIDTH^{4,11}	N/A	37"/19.5"	37"/19.5"	37"/19.5"	43"/20"	39.75"/20.5"	45.25"/22.25"	N/A	46"/25.5"	N/A	N/A	N/A	65"/30.7"	65"/30.7"
4-W LENGTH/WIDTH^{4,11}	29" WITHOUT FOOT PLATFORM/19"	N/A	39.5"/19.5"	39.5"/19.5"	43"/20"	41"/20.5"	47"/22.25"	47"/26"	46.9"/22.5"	53.25"/25.25"	56.25"/27.25"	56"	N/A	N/A
SEAT-TO-GROUND HEIGHT RANGE	N/A	19"-20"	18.13"-20.13"	18.13"-20.13"	20.5"-22"	20.75"-22.25"	20.5"-22"	21.5"-24.25"	22.5"-24.5"	24.75"-26.25"	26.25"-27.75"	27.25"	21.8"	21.8"
SEAT TYPE (STANDARD)	COMPACT, FOLDABLE (17"X15")	COMPACT, FOLDABLE (17"X15")	COMPACT, FOLDABLE (17"X17")	COMPACT, FOLDABLE (17"X17")	COMPACT, FOLDABLE (17"X17")	COMPACT, FOLDABLE (17"X17")	FOLDABLE, MOLDED PLASTIC (18"X17")	CRS RECLINING H/B W/SLIDERS & HEADREST (19"X17")	DELUXE CONTOURED MEDIUM-BACK (22"X18")	CRS RECLINING H/B W/SLIDERS & HEADREST (19"X17")	HIGH-BACK PILLOW TOP W/SLIDERS & HEADREST (19.5"X17.5")	HIGH-BACK PILLOW TOP W/SLIDERS & HEADREST (19.5"X17.5")	RECLINING H/B W/ SLIDERS & HEADREST (20"X22")	WIDE BENCH (36.5"X17.5")
(3/4-WHEEL) WEIGHT^{3,4,13}	82 LBS.	58.4 LBS.	75 LBS./78.5 LBS.	75 LBS./78.5 LBS.	83.2 LBS./99.2 LBS.	85.4 LBS./87.4 LBS.	131.5 LBS./132.5 LBS.	150 LBS.	186 LBS./192 LBS.	218.5 LBS.	259.9 LBS.	271 LBS.	253.5 LBS.	253.5 LBS.
SEAT-TO-DECK HEIGHT RANGE	N/A	16.25"-17.25"	15.75"-17.25"	15.75"-17.25"	16.25"-17.75"	16.25"-17.25"	17.5"-19"	17.25"-18.75"	16"-18"	17"-18.75"	21"-22.5"	21"-21.5"	18.7"	18.7"
BATTERY WEIGHT¹⁰	10 LBS. EA.	6 LBS. EA.	9 LBS. EA. ⁵	9 LBS. EA. ⁵ / 14 LBS. EA. ⁷	14 LBS. EA. ⁷	9 LBS. EA. ⁵ / 14 LBS. EA. ⁷	24.5 LBS. EA./ 32.5 LBS. EA.	32.5 LBS. EA.	38 LBS. EA.	38 LBS. EA.	60.5 LBS. EA.	38 LBS. EA.	75 AH: 53 LBS. EA./ 100 AH: 75.48 LBS. EA.	75 AH: 53 LBS. EA./ 100 AH: 75.48 LBS. EA.
BATTERY REQUIREMENTS⁶	(2)12AH	(2)10AH	(2)12AH	(2)12AH OR (2)18AH	(2)18AH	(2)12AH OR (2)18AH	(2) U1 OR (2) 40AH	(2) 40AH	(2) NF-22	(2) NF-22	(2) GROUP 27 OR (2) GROUP 24	(3)55AH	(2) 75AH OR (2) 100AH	(2) 75AH OR (2) 100AH
PER CHARGE RANGE (MAX.)^{2,8}	UP TO 8 MILES	UP TO 6 MILES	UP TO 8 MILES	3W: UP TO 7.2 MILES ⁹ 4W: UP TO 7.7 MILES ⁹	3W: UP TO 12.7 MILES 4W: UP TO 12 MILES	3W: UP TO 9.44 MILES 4W: UP TO 10.5 MILES	UP TO 15.5 MILES	UP TO 11 MILES	3W: UP TO 15.4 MILES 4W: UP TO 16 MILES	UP TO 14 MILES	G27: UP TO 29.51 MILES G24: UP TO 22.13 MILES	UP TO 22.5 MILES	UP TO 31.25 MILES	UP TO 32.8 MILES
BATTERY CHARGER	OFF-BOARD, 2A	OFF-BOARD, 1.5A	OFF-BOARD, 2A	OFF-BOARD, 2A	OFF-BOARD, 2A	OFF-BOARD, 2A	OFF-BOARD, 3A	OFF-BOARD, 5A	OFF-BOARD, 5A	OFF-BOARD, 5A	OFF-BOARD, 8A	36V OFF-BOARD, 8A	OFF-BOARD, 8A	OFF-BOARD, 8A
SUSPENSION	LIMITED	N/A	N/A	N/A	N/A	FRONT & REAR	N/A	N/A	3-W REAR/ 4-W FRONT & REAR	FRONT & REAR	FRONT & REAR	FRONT & REAR	FRONT & REAR	FRONT & REAR
MAXIMUM WEIGHT CAPACITY	250 LBS.	250 LBS.	260 LBS.	300 LBS.	325 LBS.	300 LBS.	400 LBS.	350 LBS.	500 LBS.	400 LBS.	400 LBS.	400 LBS.	400 LBS.	500 LBS.
STANDARD BODY COLORS	RED, BLUE	BLACK	RED	RED, BLUE ¹	RED, BLUE ¹	RED, BLUE ¹	CANDY APPLE RED, VIPER BLUE	CANDY APPLE RED, VIPER BLUE	CANDY APPLE RED, VIPER BLUE	CANDY APPLE RED, SILVER	CANDY APPLE RED, SILVER	RED, SILVER	BLACK	BLACK
WEIGHT OF HEAVIEST PIECE⁴	34.5 LBS. (REAR)	42 LBS. (3-WHEEL) (SCOOTER BASE)	29.5 LBS. (3-WHEEL) (FRONT SECTION) 34 LBS. (4-WHEEL) (FRONT SECTION)	29.5 LBS. (3-WHEEL) (FRONT SECTION) 34 LBS. (4-WHEEL) (FRONT SECTION)	36.2 LBS. (3-WHEEL) (FRONT SECTION) 52.2 LBS. (4-WHEEL) (FRONT SECTION)	34 LBS. (3-WHEEL) (FRONT SECTION) 36.6 LBS. (4-WHEEL) (FRONT SECTION)	54.5 LBS. (3-WHEEL) (FRONT SECTION) 61 LBS. (4-WHEEL) (FRONT SECTION)	68 LBS. (4-WHEEL) (FRONT SECTION)	76 LBS. (3-WHEEL) (REAR SECTION) 76 LBS. (4-WHEEL) (REAR SECTION)	95 LBS. (FRONT SECTION)	205.5 LBS. (MAIN FRAME)	216 LBS. (BASE)	203.5 LBS. (BASE WEIGHT-DOES NOT DISASSEMBLE)	203.5 LBS. (BASE WEIGHT-DOES NOT DISASSEMBLE)
MEDICARE CODE COVERAGE	N/A	K0800 - GROUP 1 STANDARD (3W)	N/A	K0800 - GROUP 1 STANDARD	K0801 - GROUP 1 HEAVY DUTY	N/A	K0801 - GROUP 1 HEAVY DUTY	N/A	K0802 - GROUP 1 VERY HEAVY DUTY (3W) K0808 - GROUP 2 ¹⁴ VERY HEAVY DUTY (4W)	N/A	N/A	N/A	N/A	N/A
WARRANTY	3-YEAR LIMITED ON FRAME; 1-YEAR LIMITED ON ELECTRONICS; 1-YEAR LIMITED ON DRIVETRAIN	3-YEAR LIMITED ON FRAME; 1-YEAR LIMITED ON ELECTRONICS; 1-YEAR LIMITED ON DRIVETRAIN	3-YEAR LIMITED ON FRAME; 1-YEAR LIMITED ON ELECTRONICS; 1-YEAR LIMITED ON DRIVETRAIN	3-YEAR LIMITED ON FRAME; 1-YEAR LIMITED ON ELECTRONICS; 1-YEAR LIMITED ON DRIVETRAIN	3-YEAR LIMITED ON FRAME; 1-YEAR LIMITED ON ELECTRONICS; 1-YEAR LIMITED ON DRIVETRAIN	3-YEAR LIMITED ON FRAME; 1-YEAR LIMITED ON ELECTRONICS; 1-YEAR LIMITED ON DRIVETRAIN	3-YEAR LIMITED ON FRAME; 1-YEAR PRO-RATA ON DRIVETRAIN; 1-YEAR LIMITED ON ELECTRONICS	3-YEAR LIMITED ON FRAME; 1-YEAR PRO-RATA ON DRIVETRAIN; 1-YEAR LIMITED ON ELECTRONICS	3-YEAR LIMITED ON FRAME; 1-YEAR PRO-RATA ON DRIVETRAIN; 1-YEAR LIMITED ON ELECTRONICS	3-YEAR LIMITED ON FRAME; 1-YEAR PRO-RATA ON DRIVETRAIN; 1-YEAR LIMITED ON ELECTRONICS	3-YEAR LIMITED ON FRAME; 1-YEAR PRO-RATA ON DRIVETRAIN; 1-YEAR LIMITED ON ELECTRONICS	3-YEAR LIMITED ON FRAME; 1-YEAR PRO-RATA ON DRIVETRAIN; 1-YEAR LIMITED ON ELECTRONICS	3-YEAR LIMITED ON FRAME; 1-YEAR PRO-RATA ON DRIVETRAIN; 1-YEAR LIMITED ON ELECTRONICS	3-YEAR LIMITED ON FRAME; 1-YEAR PRO-RATA ON DRIVETRAIN; 1-YEAR LIMITED ON ELECTRONICS
	TRAVEL MOBILITY						MID-SIZE LUXURY			HEAVY-DUTY				

The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed & range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%.